



# HARRIER 14000

## API CF-4 SAE 40

### (Heavy duty Vehicles Engine Oil)

#### **Recommended for vehicles manufactured from year 1990 to year 1994.**

QUANTUM Harrier 14000 is advanced performance SAE 40 multigrade diesel engine oil for use in the most severe on-highway and off-highway applications. It is specially engineered for modern, high-output, low-emission engines including those fitted with Exhaust Gas Recirculation (EGR) as well as older high speed turbo charged engines running on low sulphur diesel or conventional high sulphur diesel fuel.

An advanced additive system ensures excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and oxidation stability. It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness at extended drain intervals.

#### **Meets the Specifications of:**

- ACEA E2-96 Issue 5 (2007)
- API CF-4,
- API CF,
- API SG,
- MB-228.1
- MAN 271,
- MTU Type 1,
- Volvo VDS,
- Mack EO-K/2,
- Deutz DQC I-02

#### **Typical Product Performance**

Characteristics	API CF-4 SAE 40
Density @15 C, kg/l	0.886
Pour Point, C	-31
Flash Point, C	235
Kinematic Viscosity, cSt	
@ 40 C	104.11
@ 100 C	13.818
Viscosity Index	133.3
HTHS @ 150C (cP)	4.024





# HARRIER 14000

## API CF-4 SAE 40

### (Heavy duty Vehicles Engine Oil)

---

The product typical may change without notice. However, the performance of the product would meet & exceed the API & OEM requirements.

#### Customer Benefits

- Exceeds all major American, European and Japanese OEM and Industry specifications.
- Excellent performance with extended oil drains intervals on low emission engines.
- Exceptional soot dispersions, preventing deposits on critical engine components and provide excellent protection from soot induced wear.
- Excellent TBN retention effectively extends drain interval capability.
- Excellent thermal and oxidation stability that minimized low temperature sludge build-up and high temperature deposits.

#### Recommended Oil Interval Changes

Oil change intervals can be as short as 5,000 km or as long 9,000 km on some well maintained vehicles. We recommend that you follow the oil and filter change frequencies shown in your owner's manual. With the high-performance engine oil, you can have the confidence to go the full mileage or time frame recommended by the vehicle manufacturer. Harrier 14000 is especially suitable for the vehicles with extended drain intervals or vehicles with oil monitoring systems that vary oil drain intervals.

