



STEALTH 18000



Perfect Oil.
It's so perfect, we
GUARANTEE it's
Quality
Reliability
Uniqueness



"Best Quality,"

PDS

Product

| Type

**API SM SAE
5W-40**

**Fully Synthetic Passenger
Car Engine Oil**

Application

Recommended for vehicles manufactured from year 2014 with OEM Compliances.

QUANTUM Stealth 18000 is the next generation ultimate performance fully synthetic multigrade engine oil specially engineered to exceed the API SM standards meant for current and future generation high performance engines, especially those fitted with emission control devices. It is exclusively formulated with premium synthetic base fluids and unique environmentally friendly additives system to provide exceptional thermal and oxidation stability that minimizes oil thickening at very high operating temperatures, excellent deposits control and minimized engine wear and tear. An advanced additive system ensures excellent control over soot induced wear, high temperature piston deposits, corrosion, foaming and oxidation stability. It also provides excellent resistance to bore polishing, a high level of wear protection and ensures superior engine cleanliness at extended drain intervals.

Meets the Specifications of:

- | | |
|-----------------------------|-----------------------------|
| • ACEA A3/B3-08 (2008) | • API SL |
| • ACEA A3/B4-04 (2007) | • API SM |
| • ACEA A3/B4-08 (2008) | • API CF |
| • ACEA A5/B5-04 (2007) | • MB-Approval 229.1 |
| • ACEA A5/B5-08 (2008) | • MB-Approval 229.3 |
| • Renault RN0700 | • MB-Approval 229.5 |
| • Renault RN0710 | • Volkswagen VW50200 (2005) |
| • Volkswagen VW50500 (1997) | • BMW Longlife-01 |
| • Opel GM-LL-A-025 | • Opel GM-LL-B-025 |
| • Porsche | |



Product

| Type

**API SM SAE
5W-40**

**Fully Synthetic Passenger
Car Engine Oil**

Characteristics	Stealth 18000
	API SM SAE 5W-40
Density @ 15 C, kg/l	0.859
Pour Point, C	-34
Flash Point, C	223
Kinematic Viscosity, cSt	
@ 40 C	81.25
@ 100 C	14.29
Viscosity Index	183.44
Cold Cranking Visc @-30C, cP	6326.33
HTHS @ 150C (cP)	3.897

The product typical may change without notice. However, the performance of the product would meet & exceed the API & OEM requirements



Product

| Type

***API SM SAE
5W-40***

***Fully Synthetic Passenger
Car Engine Oil***

Customer Benefits

- Boost engine power and torque for better engine response and acceleration.
- Excellent fuel economy benefits, especially for the SAE 5W-40 grade.
- Ultimate engine wear protection at extreme driving conditions to prolong engine life.
- Exceptional engines cleanliness - protects against engine sludge and varnish deposits.
- Resists viscosity and thermal breakdown even in the severest service for longer drain capability.
- Excellent cold engines starting - minimize friction and wear at a start-up.

Recommended Oil Interval Changes

Oil change intervals can be as short as 30,000 km or as long 35,000 km on some new vehicles. We recommend that you follow the oil and filter change frequencies shown in your owner's manual. With the high-performance fully synthetic engine oil, you can have the confidence to go the full mileage or time frame recommended by the vehicle manufacturer. Stealth 18000 is especially suitable for the latest vehicles with extended drain intervals or vehicles with oil monitoring systems that vary oil drain intervals.